

Mr. Michael Schall
Dalton Corporation, Kendallville Manufacturing Facility
P.O. Box 271
Kendallville, IN 46755

Re: Significant Source Modification No:
113-11287-00004

Dear Mr. Schall:

Dalton Corporation, Kendallville Manufacturing Facility applied for a Part 70 operating permit on September 3, 1996 for a gray iron foundry. An application to modify the source was received on August 26, 1999. Pursuant to 326 IAC 2-7-10.5 the following emission units are approved for construction at the source:

- (a) one (1) shotblast machine, identified as #7, with a maximum capacity of 4.0 tons of metal castings per hour, with emissions controlled by a new baghouse, identified as baghouse I, and exhausting to stack I;
- (b) six (6) grinders, identified as #25-30, each with a maximum capacity of 4.0 tons of metal castings per hour, with emissions controlled by a new baghouse, identified as baghouse I, and exhausting to stack I.

The proposed Significant Source Modification approval will be incorporated into the pending Part 70 permit application pursuant to 326 IAC 2-7-10.5(l)(3). If there are no changes to the proposed construction of the emission units, the source may begin operating on the date that IDEM receives an affidavit of construction pursuant to 326 IAC 2-7-10.5(h). If there are any changes to the proposed construction the source can not operate until an Operation Permit Validation Letter is issued.

Dalton Corporation, Kendallville Manufacturing Facility
Kendallville, Indiana
00004
Permit Reviewer: Nisha Sizemore

Page 2 of 2
Source Mod #:113-11287-

This decision is subject to the Indiana Administrative Orders and Procedures Act - IC 4-21.5-3-5. If you have any questions on this matter call (800) 451-6027, press 0 and ask for Nisha Sizemore or extension 2-8356, or dial (317) 232-8356.

Sincerely,

Paul Dubenetzky, Chief
Permits Branch
Office of Air Management

Attachments

nls

cc: File - Noble County
U.S. EPA, Region V
Noble County Health Department
Air Compliance Section Inspector - Richard Sekula
Compliance Data Section - Karen Nowak
Administrative and Development - Janet Mobley
Technical Support and Modeling - Michele Boner

PART 70 SIGNIFICANT SOURCE MODIFICATION OFFICE OF AIR MANAGEMENT

**Dalton Corporation, Kendallville Manufacturing Facility
200 West Ohio Street
Kendallville, Indiana 46755**

(herein known as the Permittee) is hereby authorized to construct and operate subject to the conditions contained herein, the emission units described in Section A (Source Summary) of this approval.

This approval is issued in accordance with 326 IAC 2 and 40 CFR Part 70 Appendix A and contains the conditions and provisions specified in 326 IAC 2-7 as required by 42 U.S.C. 7401, et. seq. (Clean Air Act as amended by the 1990 Clean Air Act Amendments), 40 CFR Part 70.6, IC 13-15 and IC 13-17.

Source Modification No.: 113-11287-00004	
Issued by: Paul Dubenetzky, Branch Chief Office of Air Management	Issuance Date:

TABLE OF CONTENTS

A	SOURCE SUMMARY	3
A.1	General Information [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)]	
A.2	Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)]	
A.3	Part 70 Permit Applicability [326 IAC 2-7-2]	
B	GENERAL CONSTRUCTION CONDITIONS	4
B.1	Permit No Defense [IC 13]	
B.2	Definitions [326 IAC 2-7-1]	
B.3	Effective Date of the Permit [IC13-15-5-3]	
B.4	Revocation of Permits [326 IAC 2-1.1-9(5)][326 IAC 2-7-10.5(i)]	
B.5	Significant Source Modification [326 IAC 2-7-10.5(h)]	
B.6	Emergency Provisions [326 IAC 2-7-16]	
C	GENERAL OPERATION CONDITIONS	7
C.1	Certification [326 IAC 2-7-4(f)] [326 IAC 2-7-6(1)]	
C.2	Preventive Maintenance Plan [326 IAC 2-7-5(1),(3) and (13)] [326 IAC 2-7-6(1) and (6)]	
C.3	Permit Amendment or Modification [326 IAC 2-7-11] [326 IAC 2-7-12]	
C.4	Opacity [326 IAC 5-1]	
C.5	Operation of Equipment [326 IAC 2-7-6(6)]	
C.6	Stack Height [326 IAC 1-7]	
C.7	Performance Testing [326 IAC 3-6]	
C.8	Compliance Monitoring [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]	
C.9	Maintenance of Monitoring Equipment [326 IAC 2-7-5(3)(A)(iii)]	
C.10	Compliance Monitoring Plan - Failure to Take Response Steps	
C.11	Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-7-5]	
C.12	Monitoring Data Availability [326 IAC 2-7-6(1)] [326 IAC 2-7-5(3)]	
C.13	General Record Keeping Requirements [326 IAC 2-7-5(3)]	
C.14	General Reporting Requirements [326 IAC 2-7-5(3)(C)]	
D.1	FACILITY OPERATION CONDITIONS - Baghouse I controlling shotblast machine #7 and grinders #25 - 30	14
	Certification	18

SECTION A

SOURCE SUMMARY

This approval is based on information requested by the Indiana Department of Environmental Management (IDEM), Office of Air Management (OAM) . The information describing the emission units contained in conditions A.1 through A.2 is descriptive information and does not constitute enforceable conditions. However, the Permittee should be aware that a physical change or a change in the method of operation that may render this descriptive information obsolete or inaccurate may trigger requirements for the Permittee to obtain additional permits or seek modification of this approval pursuant to 326 IAC 2, or change other applicable requirements presented in the permit application.

A.1 General Information [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)]

The Permittee owns and operates stationary gray iron foundry.

Responsible Official: Daniel E. Hirsch, Plant Manager
Source Address: 200 West Ohio Street, Kendallville, Indiana 46755
Mailing Address: P.O. Box 271, Kendallville, Indiana 46755
Phone Number: Daniel E. Hirsch: (219) 347-1820
SIC Code: 3321
County Location: Noble
County Status: Attainment for all criteria pollutants
Source Status: Part 70 Permit Program
Major Source under PSD Rules;
Major Source, Section 112 of the Clean Air Act

A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)] [326 IAC 2-7-5(15)]

This stationary source is approved to construct and operate the following emission units and pollution control devices:

- (a) one (1) shotblast machine, identified as #7, with a maximum capacity of 4.0 tons of metal castings per hour, with emissions controlled by a new baghouse, identified as baghouse I, and exhausting to stack I;
- (b) six (6) grinders, identified as #25-30, each with a maximum capacity of 4.0 tons of metal castings per hour, with emissions controlled by a new baghouse, identified as baghouse I, and exhausting to stack I.

A.3 Part 70 Permit Applicability [326 IAC 2-7-2]

This stationary source is required to have a Part 70 permit by 326 IAC 2-7-2 (Applicability) because:

- (a) It is a major source, as defined in 326 IAC 2-7-1(22); and
- (b) It is a source in a source category designated by the United States Environmental Protection Agency (U.S. EPA) under 40 CFR 70.3 (Part 70 - Applicability).

SECTION B GENERAL CONSTRUCTION CONDITIONS

B.1 Permit No Defense [IC 13]

This approval to construct does not relieve the Permittee of the responsibility to comply with the provisions of the Indiana Environmental Management Law (IC 13-11 through 13-20; 13-22 through 13-25; and 13-30), the Air Pollution Control Law (IC 13-17) and the rules promulgated thereunder, as well as other applicable local, state, and federal requirements.

B.2 Definitions [326 IAC 2-7-1]

Terms in this approval shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, any applicable definitions found in IC 13-11, 326 IAC 1-2 and 326 IAC 2-7 shall prevail.

B.3 Effective Date of the Permit [IC13-15-5-3]

Pursuant to IC 13-15-5-3, this approval becomes effective upon its issuance.

B.4 Revocation of Permits [326 IAC 2-1.1-9(5)][326 IAC 2-7-10.5(i)]

Pursuant to 326 IAC 2-1.1-9(5)(Revocation of Permits), the Commissioner may revoke this approval if construction is not commenced within eighteen (18) months after receipt of this approval or if construction is suspended for a continuous period of one (1) year or more.

B.5 Significant Source Modification [326 IAC 2-7-10.5(h)]

This document shall also become the approval to operate pursuant to 326 IAC 2-7-10.5(h) when, prior to start of operation, the following requirements are met:

- (a) The attached affidavit of construction shall be submitted to the Office of Air Management (OAM), Permit Administration & Development Section, verifying that the emission units were constructed as proposed in the application. The emissions units covered in the Significant Source Modification approval may begin operating on the date the affidavit of construction is postmarked or hand delivered to IDEM if constructed as proposed.
- (b) If actual construction of the emissions units differs from the construction proposed in the application, the source may not begin operation until the source modification has been revised pursuant to 326 IAC 2-7-11 or 326 IAC 2-7-12 and an Operation Permit Validation Letter is issued.
- (c) If construction is completed in phases; i.e., the entire construction is not done continuously, a separate affidavit must be submitted for each phase of construction. Any permit conditions associated with operation start up dates such as stack testing for New Source Performance Standards (NSPS) shall be applicable to each individual phase.
- (d) The Permittee shall receive an Operation Permit Validation Letter from the Chief of the Permit Administration & Development Section and attach it to this document.

B.6 Emergency Provisions [326 IAC 2-7-16]

- (a) An emergency, as defined in 326 IAC 2-7-1(12), is not an affirmative defense for an action brought for noncompliance with a federal or state health-based emission limitation, except as provided in 326 IAC 2-7-16.
- (b) An emergency, as defined in 326 IAC 2-7-1(12), constitutes an affirmative defense to an action brought for noncompliance with a health-based or technology-based emission limitation if the affirmative defense of an emergency is demonstrated through properly

signed, contemporaneous operating logs or other relevant evidence that describe the following:

- (1) An emergency occurred and the Permittee can, to the extent possible, identify the causes of the emergency;
- (2) The permitted facility was at the time being properly operated;
- (3) During the period of an emergency, the Permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards or other requirements in this permit;
- (4) For each emergency lasting one (1) hour or more, the Permittee notified IDEM, OAM, within four (4) daytime business hours after the beginning of the emergency, or after the emergency was discovered or reasonably should have been discovered;

Telephone Number: 1-800-451-6027 (ask for Office of Air Management, Compliance Section), or
Telephone Number: 317-233-5674 (ask for Compliance Section)
Facsimile Number: 317-233-5967

- (5) For each emergency lasting one (1) hour or more, the Permittee submitted notice, either in writing or facsimile, of the emergency to:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Management
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

within two (2) working days of the time when emission limitations were exceeded due to the emergency.

The notice fulfills the requirement of 326 IAC 2-7-5(3)(C)(ii) and must contain the following:

- (A) A description of the emergency;
- (B) Any steps taken to mitigate the emissions; and
- (C) Corrective actions taken.

The notification which shall be submitted by the Permittee does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (6) The Permittee immediately took all reasonable steps to correct the emergency.
- (c) In any enforcement proceeding, the Permittee seeking to establish the occurrence of an emergency has the burden of proof.

- (d) This emergency provision supersedes 326 IAC 1-6 (Malfunctions) for sources subject to this rule after the effective date of this rule. This permit condition is in addition to any emergency or upset provision contained in any applicable requirement.
- (e) IDEM, OAM, may require that the Preventive Maintenance Plans required under 326 IAC 2-7-4-(c)(9) be revised in response to an emergency.
- (f) Failure to notify IDEM, OAM, by telephone or facsimile of an emergency lasting more than one (1) hour in compliance with (b)(4) and (5) of this condition shall constitute a violation of 326 IAC 2-7 and any other applicable rules.
- (g) Operations may continue during an emergency only if the following conditions are met:
 - (1) If the emergency situation causes a deviation from a technology-based limit, the Permittee may continue to operate the affected emitting facilities during the emergency provided the Permittee immediately takes all reasonable steps to correct the emergency and minimize emissions.
 - (2) If an emergency situation causes a deviation from a health-based limit, the Permittee may not continue to operate the affected emissions facilities unless:
 - (A) The Permittee immediately takes all reasonable steps to correct the emergency situation and to minimize emissions; and
 - (B) Continued operation of the facilities is necessary to prevent imminent injury to persons, severe damage to equipment, substantial loss of capital investment, or loss of product or raw materials of substantial economic value.

Any operation shall continue no longer than the minimum time required to prevent the situations identified in (g)(2)(B) of this condition.

SECTION C GENERAL OPERATION CONDITIONS

C.1 Certification [326 IAC 2-7-4(f)] [326 IAC 2-7-6(1)]

- (a) Where specifically designated by this approval or required by an applicable requirement, any application form, report, or compliance certification submitted under this approval shall contain certification by a responsible official of truth, accuracy, and completeness. This certification, and any other certification required under this approval, shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.
- (b) One (1) certification shall be included, on the attached Certification Form, with each submittal.
- (c) A responsible official is defined at 326 IAC 2-7-1(34).

C.2 Preventive Maintenance Plan [326 IAC 2-7-5(1),(3) and (13)] [326 IAC 2-7-6(1) and (6)] [326 IAC 1-6-3]

- (a) If required by specific condition(s) in Section D of this approval, the Permittee shall prepare and maintain Preventive Maintenance Plans (PMP) within ninety (90) days after issuance of this approval, including the following information on each facility:
 - (1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;
 - (2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions;
 - (3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.

If due to circumstances beyond its control, the PMP cannot be prepared and maintained within the above time frame, the Permittee may extend the date an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Management
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

- (b) The Permittee shall implement the Preventive Maintenance Plans as necessary to ensure that lack of proper maintenance does not cause or contribute to a violation of any limitation on emissions or potential to emit.
- (c) PMP's shall be submitted to IDEM, OAM, upon request and shall be subject to review and approval by IDEM, OAM, .

C.3 Permit Amendment or Modification [326 IAC 2-7-11] [326 IAC 2-7-12]

- (a) The Permittee must comply with the requirements of 326 IAC 2-7-11 or 326 IAC 2-7-12 whenever the Permittee seeks to amend or modify this approval.

- (b) Any application requesting an amendment or modification of this approval shall be submitted to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Management
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

Any such application should be certified by the "responsible official" as defined by 326 IAC 2-7-1(34) only if a certification is required by the terms of the applicable rule

- (c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-7-11(c)(3)]

C.4 Opacity [326 IAC 5-1]

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Exemptions), opacity shall meet the following, unless otherwise stated in this approval:

- (a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings) as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

C.5 Operation of Equipment [326 IAC 2-7-6(6)]

All air pollution control equipment listed in this approval and used to comply with an applicable requirement shall be operated at all times that the emission units vented to the control equipment are in operation.

C.6 Stack Height [326 IAC 1-7]

The Permittee shall comply with the applicable provisions of 326 IAC 1-7 (Stack Height Provisions), for all exhaust stacks through which a potential (before controls) of twenty-five (25) tons per year or more of particulate matter or sulfur dioxide is emitted by using good engineering practices (GEP) pursuant to 326 IAC 1-7-3.

Testing Requirements [326 IAC 2-7-6(1)]

C.7 Performance Testing [326 IAC 3-6]

- (a) All testing shall be performed according to the provisions of 326 IAC 3-6 (Source Sampling Procedures), except as provided elsewhere in this approval, utilizing methods approved by IDEM, OAM.

A test protocol, except as provided elsewhere in this approval, shall be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Management

100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

no later than thirty-five (35) days prior to the intended test date. The Permittee shall submit a notice of the actual test date to the above address so that it is received at least two weeks prior to the test date.

- (b) All test reports must be received by IDEM, OAM within forty-five (45) days after the completion of the testing. An extension may be granted by the Commissioner, if the source submits to IDEM, OAM, a reasonable written explanation within five (5) days prior to the end of the initial forty-five (45) day period.

The documentation submitted by the Permittee does not require certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

Compliance Monitoring Requirements [326 IAC 2-7-5(1)] [326 IAC 2-7-6(1)]

C.8 Compliance Monitoring [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]

Compliance with applicable requirements shall be documented as required by this approval. The Permittee shall be responsible for installing any necessary equipment and initiating any required monitoring related to that equipment, no more than ninety (90) days after receipt of this approval. If due to circumstances beyond its control, this schedule cannot be met, the Permittee may extend the compliance schedule an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Management
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

in writing, prior to the end of the initial ninety (90) day compliance schedule, with full justification of the reasons for the inability to meet this date.

The notification which shall be submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

Corrective Actions and Response Steps [326 IAC 2-7-5] [326 IAC 2-7-6]

C.9 Compliance Monitoring Plan - Failure to Take Response Steps [326 IAC 2-7-5][326 IAC 2-7-6] [326 IAC 1-6]

- (a) The Permittee is required to implement a compliance monitoring plan to ensure that reasonable information is available to evaluate its continuous compliance with applicable requirements. This compliance monitoring plan is comprised of:
- (1) This condition;
 - (2) The Compliance Determination Requirements in Section D of this approval;
 - (3) The Compliance Monitoring Requirements in Section D of this approval;

- (4) The Record Keeping and Reporting Requirements in Section C (Monitoring Data Availability, General Record Keeping Requirements, and General Reporting Requirements) and in Section D of this approval; and
- (5) A Compliance Response Plan (CRP) for each compliance monitoring condition of this approval. CRP's shall be submitted to IDEM, OAM upon request and shall be subject to review and approval by IDEM, OAM, . The CRP shall be prepared within ninety (90) days after issuance of this approval by the Permittee and maintained on site, and is comprised of :
 - (A) Response steps that will be implemented in the event that compliance related information indicates that a response step is needed pursuant to the requirements of Section D of this approval; and
 - (B) A time schedule for taking such response steps including a schedule for devising additional response steps for situations that may not have been predicted.
- (b) For each compliance monitoring condition of this approval, appropriate response steps shall be taken when indicated by the provisions of that compliance monitoring condition. Failure to perform the actions detailed in the compliance monitoring conditions or failure to take the response steps within the time prescribed in the Compliance Response Plan, shall constitute a violation of the approval unless taking the response steps set forth in the Compliance Response Plan would be unreasonable.
- (c) After investigating the reason for the excursion, the Permittee is excused from taking further response steps for any of the following reasons:
 - (1) The monitoring equipment malfunctioned, giving a false reading. This shall be an excuse from taking further response steps providing that prompt action was taken to correct the monitoring equipment.
 - (2) The Permittee has determined that the compliance monitoring parameters established in the approval conditions are technically inappropriate, has previously submitted a request for an administrative amendment to the approval, and such request has not been denied or;
 - (3) An automatic measurement was taken when the process was not operating; or
 - (4) The process has already returned to operating within "normal" parameters and no response steps are required.
- (d) Records shall be kept of all instances in which the compliance related information was not met and of all response steps taken. In the event of an emergency, the provisions of 326 IAC 2-7-16 (Emergency Provisions) requiring prompt corrective action to mitigate emissions shall prevail.

-
- (a) When the results of a stack test performed in conformance with Section C - Performance Testing, of this approval exceed the level specified in any condition of this approval, the Permittee shall take appropriate corrective actions. The Permittee shall submit a description of these corrective actions to IDEM, OAM, within thirty (30) days of receipt of the test results. The Permittee shall take appropriate action to minimize emissions from the affected facility while the corrective actions are being implemented. IDEM, OAM shall notify the Permittee within thirty (30) days, if the corrective actions taken are deficient. The Permittee shall submit a description of additional corrective actions taken to IDEM, OAM within thirty (30) days of receipt of the notice of deficiency. IDEM, OAM reserves the authority to use enforcement activities to resolve noncompliant stack tests.
- (b) A retest to demonstrate compliance shall be performed within one hundred twenty (120) days of receipt of the original test results. Should the Permittee demonstrate to IDEM, OAM that retesting in one-hundred and twenty (120) days is not practicable, IDEM, OAM may extend the retesting deadline. Failure of the second test to demonstrate compliance with the appropriate approval conditions may be grounds for immediate revocation of the approval to operate the affected facility.

The documents submitted pursuant to this condition do not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

C.11 Monitoring Data Availability [326 IAC 2-7-6(1)] [326 IAC 2-7-5(3)]

- (a) With the exception of performance tests conducted in accordance with Section C- Performance Testing, all observations, sampling, maintenance procedures, and record keeping, required as a condition of this approval shall be performed at all times the equipment is operating at normal representative conditions.
- (b) As an alternative to the observations, sampling, maintenance procedures, and record keeping of subsection (a) above, when the equipment listed in Section D of this approval is not operating, the Permittee shall either record the fact that the equipment is shut down or perform the observations, sampling, maintenance procedures, and record keeping that would otherwise be required by this approval.
- (c) If the equipment is operating but abnormal conditions prevail, additional observations and sampling should be taken with a record made of the nature of the abnormality.
- (d) If for reasons beyond its control, the operator fails to make required observations, sampling, maintenance procedures, or record keeping, reasons for this must be recorded.
- (e) At its discretion, IDEM may excuse such failure providing adequate justification is documented and such failures do not exceed five percent (5%) of the operating time in any quarter.
- (f) Temporary, unscheduled unavailability of staff qualified to perform the required observations, sampling, maintenance procedures, or record keeping shall be considered a valid reason for failure to perform the requirements stated in (a) above.

C.12 General Record Keeping Requirements [326 IAC 2-7-5(3)][326 IAC 2-7-6]

-
- (a) Records of all required monitoring data and support information shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be kept at the source location for a minimum of three (3) years and available upon the request of an IDEM, OAM, representative.

The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a written request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.

- (b) Records of required monitoring information shall include, where applicable:
- (1) The date, place, and time of sampling or measurements;
 - (2) The dates analyses were performed;
 - (3) The company or entity performing the analyses;
 - (4) The analytic techniques or methods used;
 - (5) The results of such analyses; and
 - (6) The operating conditions existing at the time of sampling or measurement.
- (c) Support information shall include, where applicable:
- (1) Copies of all reports required by this approval;
 - (2) All original strip chart recordings for continuous monitoring instrumentation;
 - (3) All calibration and maintenance records;
 - (4) Records of preventive maintenance shall be sufficient to demonstrate that improper maintenance did not cause or contribute to a violation of any limitation on emissions or potential to emit. To be relied upon subsequent to any such violation, these records may include, but are not limited to: work orders, parts inventories, and operator's standard operating procedures. Records of response steps taken shall indicate whether the response steps were performed in accordance with the Compliance Response Plan required by Section C - Compliance Monitoring Plan - Failure to take Response Steps, of this approval, and whether a deviation from a approval condition was reported. All records shall briefly describe what maintenance and response steps were taken and indicate who performed the tasks.
- (d) All record keeping requirements not already legally required shall be implemented within ninety (90) days of approval issuance.

C.13 General Reporting Requirements [326 IAC 2-7-5(3)(C)]

- (a) The reports required by conditions in Section D of this approval shall be submitted to:

Indiana Department of Environmental Management

Compliance Data Section, Office of Air Management
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

- (b) Unless otherwise specified in this approval, any notice, report, or other submission required by this approval shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAM, on or before the date it is due.
- (c) Unless otherwise specified in this approval, any quarterly report shall be submitted within thirty (30) days of the end of the reporting period. The report do not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (d) The first report shall cover the period commencing on the date of issuance of this approval and ending on the last day of the reporting period.

SECTION D.1 FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]

- (a) one (1) shotblast machine, identified as #7, with a maximum capacity of 4.0 tons of metal castings per hour, with emissions controlled by a new baghouse, identified as baghouse I, and exhausting to stack I; and
- (b) six (6) grinders, identified as #25-30, each with a maximum capacity of 4.0 tons of metal castings per hour, with emissions controlled by a new baghouse, identified as baghouse I, and exhausting to stack I.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.1.1 Particulate Matter (PM) [326 IAC 6-3]

Pursuant to 326 IAC 6-3-2 (Process Operations), the particulate matter (PM) from the shotblaster and each of the grinders shall not exceed 10.4 pounds per hour when operating at a process weight rate of 4.0 tons of metal castings per hour each. The pounds per hour limitation was calculated with the following equation:

Interpolation and extrapolation of the data for the process weight rate up to 60,000 pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67} \quad \text{where } E = \text{rate of emission in pounds per hour; and} \\ P = \text{process weight rate in tons per hour}$$

D.1.2 Prevention of Significant Deterioration (PSD) [326 IAC 2-2]

In order to render the requirements of 326 IAC 2-2 (PSD) and 40 CFR 52.21 not applicable, the following conditions shall apply:

- (a) The PM emissions from the baghouse I controlling the shot blast machine #7 and grinders #25 - 30 shall not exceed 5.48 pounds per hour.
- (b) The PM10 emissions from the baghouse I controlling the shot blast machine #7 and grinders #25 - 30 shall not exceed 3.20 pounds per hour.

Therefore, the requirements of 326 IAC 2-2 (PSD) and 40 CFR 52.21 shall not apply.

D.1.3 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for these facilities.

Compliance Determination Requirements

D.1.4 Testing Requirements [326 IAC 2-7-6(1),(6)]

The Permittee is not required to test these facilities by this permit. However IDEM may require compliance testing when necessary to determine if the facilities are in compliance. If testing is required by IDEM, compliance with the PM and PM10 limits specified in Conditions D.1.1 and D.1.2 shall be determined by a performance test conducted in accordance with Section C - Performance Testing.

D.1.5 Particulate Matter (PM)

The baghouse identified as I for PM and PM10 control shall be in operation and control emissions from the shotblast machine #7 and grinders #25 - 30 at all times when these processes are in operation.

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

D.1.6 Visible Emissions Notations

- (a) Visible emission notations of each of the baghouse I stack exhaust shall be performed once per shift during normal daylight operations when exhausting to the atmosphere. A trained employee shall record whether emissions are normal or abnormal.
- (b) For processes operated continuously, "normal" means those conditions prevailing, or expected to prevail, eighty percent (80%) of the time the process is in operation, not counting startup or shut down time.
- (c) In the case of batch or discontinuous operations, readings shall be taken during that part of the operation that would normally be expected to cause the greatest emissions.
- (d) A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the appearance and characteristics of normal visible emissions for that specific process.
- (e) The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when an abnormal emission is observed.

D.1.7 Parametric Monitoring

The Permittee shall record the total static pressure drop across the baghouse I used in conjunction with the shotblast machine #7 and grinders #25 - 30, at least once daily when the shotblaster and the grinders are in operation when venting to the atmosphere. Unless operated under conditions for which the Compliance Response Plan specifies otherwise, the pressure drop across each of the baghouses shall be maintained within the range of 3.0 and 8.0 inches of water or a range established during the latest stack test. The Compliance Response Plan for these units shall contain troubleshooting contingency and response steps for when the pressure reading is outside of the above mentioned range for any one reading.

The instrument used for determining the pressure shall comply with Section C - Pressure Gauge Specifications, of this permit, shall be subject to approval by IDEM, OAM, and shall be calibrated at least once every six (6) months.

D.1.8 Baghouse Inspections

An inspection shall be performed each calendar quarter of all bags controlling the shotblast machine #7 and grinders #25 - 30 when venting to the atmosphere. A baghouse inspection shall be performed within three months of redirecting vents to the atmosphere and every three months thereafter. Inspections are optional when venting indoors. All defective bags shall be replaced.

D.1.9 Broken or Failed Bag Detection

In the event that bag failure has been observed.

- (a) The affected compartments will be shut down immediately until the failed units have been repaired or replaced. Within eight (8) hours of the determination of failure, response steps according to the timetable described in the Compliance Response Plan shall be initiated. For any failure with corresponding response steps and timetable not described in the Compliance Response Plan, response steps shall be devised within eight (8) hours of discovery of the failure and shall include a timetable for completion. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions).
- (b) For single compartment baghouses, failed units and the associated process will be shut down immediately until the failed units have been repaired or replaced. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions).

Record Keeping and Reporting Requirement [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.1.10 Record Keeping Requirements

- (a) To document compliance with Condition D.1.6, the Permittee shall maintain records of visible emission notations of the baghouse stack exhaust once per shift.
- (b) To document compliance with Condition D.1.7, the Permittee shall maintain the following:
 - (1) Daily records of the following operational parameters during normal operation when venting to the atmosphere:
 - (A) Inlet and outlet differential static pressure; and
 - (B) Cleaning cycle: frequency and differential pressure.
 - (2) Documentation of all response steps implemented, per event .
 - (3) Operation and Compliance Response logs, including work purchases orders, shall be maintained.
 - (4) Quality Assurance/Quality Control (QA/QC) procedures.
 - (5) Operator standard operating procedures (SOP).
 - (6) Manufacturer's specifications or its equivalent.

- (7) Equipment "troubleshooting" contingency plan.
- (8) Documentation of the dates vents are redirected.
- (c) To document compliance with Condition D.1.8, the Permittee shall maintain records of the results of the inspections required under Condition D.1.8 and the dates the vents are redirected.
- (d) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR MANAGEMENT
COMPLIANCE DATA SECTION**

**PART 70 SOURCE MODIFICATION
CERTIFICATION**

Source Name: Dalton Corporation, Kendallville Manufacturing Facility
Source Address: 200 West Ohio Street, Kendallville, Indiana 46755
Mailing Address: P.O. Box 271, Kendallville, Indiana 46755
Source Modification No.: 113-11287-00004

This certification shall be included when submitting monitoring, testing reports/results or other documents as required by this approval.

Please check what document is being certified:

- 9 Test Result (specify) _____
- 9 Report (specify) _____
- 9 Notification (specify) _____
- 9 Other (specify) _____

I certify that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

Signature:

Printed Name:

Title/Position:

Date:

PART 70 SIGNIFICANT SOURCE MODIFICATION OFFICE OF AIR MANAGEMENT

**Dalton Corporation, Kendallville Manufacturing Facility
200 West Ohio Street
Kendallville, Indiana 46755**

(herein known as the Permittee) is hereby authorized to construct and operate subject to the conditions contained herein, the emission units described in Section A (Source Summary) of this approval.

This approval is issued in accordance with 326 IAC 2 and 40 CFR Part 70 Appendix A and contains the conditions and provisions specified in 326 IAC 2-7 as required by 42 U.S.C. 7401, et. seq. (Clean Air Act as amended by the 1990 Clean Air Act Amendments), 40 CFR Part 70.6, IC 13-15 and IC 13-17.

Source Modification No.: 113-11287-00004	
Issued by: Paul Dubenetzky, Branch Chief Office of Air Management	Issuance Date:

TABLE OF CONTENTS

A	SOURCE SUMMARY	3
A.1	General Information [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)]	
A.2	Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)]	
A.3	Part 70 Permit Applicability [326 IAC 2-7-2]	
B	GENERAL CONSTRUCTION CONDITIONS	4
B.1	Permit No Defense [IC 13]	
B.2	Definitions [326 IAC 2-7-1]	
B.3	Effective Date of the Permit [IC13-15-5-3]	
B.4	Revocation of Permits [326 IAC 2-1.1-9(5)][326 IAC 2-7-10.5(i)]	
B.5	Significant Source Modification [326 IAC 2-7-10.5(h)]	
B.6	Emergency Provisions [326 IAC 2-7-16]	
C	GENERAL OPERATION CONDITIONS	7
C.1	Certification [326 IAC 2-7-4(f)] [326 IAC 2-7-6(1)]	
C.2	Preventive Maintenance Plan [326 IAC 2-7-5(1),(3) and (13)] [326 IAC 2-7-6(1) and (6)]	
C.3	Permit Amendment or Modification [326 IAC 2-7-11] [326 IAC 2-7-12]	
C.4	Opacity [326 IAC 5-1]	
C.5	Operation of Equipment [326 IAC 2-7-6(6)]	
C.6	Stack Height [326 IAC 1-7]	
C.7	Performance Testing [326 IAC 3-6]	
C.8	Compliance Monitoring [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]	
C.9	Maintenance of Monitoring Equipment [326 IAC 2-7-5(3)(A)(iii)]	
C.10	Compliance Monitoring Plan - Failure to Take Response Steps	
C.11	Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-7-5]	
C.12	Monitoring Data Availability [326 IAC 2-7-6(1)] [326 IAC 2-7-5(3)]	
C.13	General Record Keeping Requirements [326 IAC 2-7-5(3)]	
C.14	General Reporting Requirements [326 IAC 2-7-5(3)(C)]	
D.1	FACILITY OPERATION CONDITIONS - Baghouse I controlling shotblast machine #7 and grinders #25 - 30	14
	Certification	18

SECTION A

SOURCE SUMMARY

This approval is based on information requested by the Indiana Department of Environmental Management (IDEM), Office of Air Management (OAM) . The information describing the emission units contained in conditions A.1 through A.2 is descriptive information and does not constitute enforceable conditions. However, the Permittee should be aware that a physical change or a change in the method of operation that may render this descriptive information obsolete or inaccurate may trigger requirements for the Permittee to obtain additional permits or seek modification of this approval pursuant to 326 IAC 2, or change other applicable requirements presented in the permit application.

A.1 General Information [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)]

The Permittee owns and operates stationary gray iron foundry.

Responsible Official: Daniel E. Hirsch, Plant Manager
Source Address: 200 West Ohio Street, Kendallville, Indiana 46755
Mailing Address: P.O. Box 271, Kendallville, Indiana 46755
Phone Number: Daniel E. Hirsch: (219) 347-1820
SIC Code: 3321
County Location: Noble
County Status: Attainment for all criteria pollutants
Source Status: Part 70 Permit Program
Major Source under PSD Rules;
Major Source, Section 112 of the Clean Air Act

A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)] [326 IAC 2-7-5(15)]

This stationary source is approved to construct and operate the following emission units and pollution control devices:

- (a) one (1) shotblast machine, identified as #7, with a maximum capacity of 4.0 tons of metal castings per hour, with emissions controlled by a new baghouse, identified as baghouse I, and exhausting to stack I;
- (b) six (6) grinders, identified as #25-30, each with a maximum capacity of 4.0 tons of metal castings per hour, with emissions controlled by a new baghouse, identified as baghouse I, and exhausting to stack I.

A.3 Part 70 Permit Applicability [326 IAC 2-7-2]

This stationary source is required to have a Part 70 permit by 326 IAC 2-7-2 (Applicability) because:

- (a) It is a major source, as defined in 326 IAC 2-7-1(22); and
- (b) It is a source in a source category designated by the United States Environmental Protection Agency (U.S. EPA) under 40 CFR 70.3 (Part 70 - Applicability).

SECTION B GENERAL CONSTRUCTION CONDITIONS

B.1 Permit No Defense [IC 13]

This approval to construct does not relieve the Permittee of the responsibility to comply with the provisions of the Indiana Environmental Management Law (IC 13-11 through 13-20; 13-22 through 13-25; and 13-30), the Air Pollution Control Law (IC 13-17) and the rules promulgated thereunder, as well as other applicable local, state, and federal requirements.

B.2 Definitions [326 IAC 2-7-1]

Terms in this approval shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, any applicable definitions found in IC 13-11, 326 IAC 1-2 and 326 IAC 2-7 shall prevail.

B.3 Effective Date of the Permit [IC13-15-5-3]

Pursuant to IC 13-15-5-3, this approval becomes effective upon its issuance.

B.4 Revocation of Permits [326 IAC 2-1.1-9(5)][326 IAC 2-7-10.5(i)]

Pursuant to 326 IAC 2-1.1-9(5)(Revocation of Permits), the Commissioner may revoke this approval if construction is not commenced within eighteen (18) months after receipt of this approval or if construction is suspended for a continuous period of one (1) year or more.

B.5 Significant Source Modification [326 IAC 2-7-10.5(h)]

This document shall also become the approval to operate pursuant to 326 IAC 2-7-10.5(h) when, prior to start of operation, the following requirements are met:

- (a) The attached affidavit of construction shall be submitted to the Office of Air Management (OAM), Permit Administration & Development Section, verifying that the emission units were constructed as proposed in the application. The emissions units covered in the Significant Source Modification approval may begin operating on the date the affidavit of construction is postmarked or hand delivered to IDEM if constructed as proposed.
- (b) If actual construction of the emissions units differs from the construction proposed in the application, the source may not begin operation until the source modification has been revised pursuant to 326 IAC 2-7-11 or 326 IAC 2-7-12 and an Operation Permit Validation Letter is issued.
- (c) If construction is completed in phases; i.e., the entire construction is not done continuously, a separate affidavit must be submitted for each phase of construction. Any permit conditions associated with operation start up dates such as stack testing for New Source Performance Standards (NSPS) shall be applicable to each individual phase.
- (d) The Permittee shall receive an Operation Permit Validation Letter from the Chief of the Permit Administration & Development Section and attach it to this document.

B.6 Emergency Provisions [326 IAC 2-7-16]

- (a) An emergency, as defined in 326 IAC 2-7-1(12), is not an affirmative defense for an action brought for noncompliance with a federal or state health-based emission limitation, except as provided in 326 IAC 2-7-16.
- (b) An emergency, as defined in 326 IAC 2-7-1(12), constitutes an affirmative defense to an action brought for noncompliance with a health-based or technology-based emission limitation if the affirmative defense of an emergency is demonstrated through properly

signed, contemporaneous operating logs or other relevant evidence that describe the following:

- (1) An emergency occurred and the Permittee can, to the extent possible, identify the causes of the emergency;
- (2) The permitted facility was at the time being properly operated;
- (3) During the period of an emergency, the Permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards or other requirements in this permit;
- (4) For each emergency lasting one (1) hour or more, the Permittee notified IDEM, OAM, within four (4) daytime business hours after the beginning of the emergency, or after the emergency was discovered or reasonably should have been discovered;

Telephone Number: 1-800-451-6027 (ask for Office of Air Management, Compliance Section), or
Telephone Number: 317-233-5674 (ask for Compliance Section)
Facsimile Number: 317-233-5967

- (5) For each emergency lasting one (1) hour or more, the Permittee submitted notice, either in writing or facsimile, of the emergency to:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Management
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

within two (2) working days of the time when emission limitations were exceeded due to the emergency.

The notice fulfills the requirement of 326 IAC 2-7-5(3)(C)(ii) and must contain the following:

- (A) A description of the emergency;
- (B) Any steps taken to mitigate the emissions; and
- (C) Corrective actions taken.

The notification which shall be submitted by the Permittee does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (6) The Permittee immediately took all reasonable steps to correct the emergency.
- (c) In any enforcement proceeding, the Permittee seeking to establish the occurrence of an emergency has the burden of proof.

- (d) This emergency provision supersedes 326 IAC 1-6 (Malfunctions) for sources subject to this rule after the effective date of this rule. This permit condition is in addition to any emergency or upset provision contained in any applicable requirement.
- (e) IDEM, OAM, may require that the Preventive Maintenance Plans required under 326 IAC 2-7-4-(c)(9) be revised in response to an emergency.
- (f) Failure to notify IDEM, OAM, by telephone or facsimile of an emergency lasting more than one (1) hour in compliance with (b)(4) and (5) of this condition shall constitute a violation of 326 IAC 2-7 and any other applicable rules.
- (g) Operations may continue during an emergency only if the following conditions are met:
 - (1) If the emergency situation causes a deviation from a technology-based limit, the Permittee may continue to operate the affected emitting facilities during the emergency provided the Permittee immediately takes all reasonable steps to correct the emergency and minimize emissions.
 - (2) If an emergency situation causes a deviation from a health-based limit, the Permittee may not continue to operate the affected emissions facilities unless:
 - (A) The Permittee immediately takes all reasonable steps to correct the emergency situation and to minimize emissions; and
 - (B) Continued operation of the facilities is necessary to prevent imminent injury to persons, severe damage to equipment, substantial loss of capital investment, or loss of product or raw materials of substantial economic value.

Any operation shall continue no longer than the minimum time required to prevent the situations identified in (g)(2)(B) of this condition.

SECTION C GENERAL OPERATION CONDITIONS

C.1 Certification [326 IAC 2-7-4(f)] [326 IAC 2-7-6(1)]

- (a) Where specifically designated by this approval or required by an applicable requirement, any application form, report, or compliance certification submitted under this approval shall contain certification by a responsible official of truth, accuracy, and completeness. This certification, and any other certification required under this approval, shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.
- (b) One (1) certification shall be included, on the attached Certification Form, with each submittal.
- (c) A responsible official is defined at 326 IAC 2-7-1(34).

C.2 Preventive Maintenance Plan [326 IAC 2-7-5(1),(3) and (13)] [326 IAC 2-7-6(1) and (6)] [326 IAC 1-6-3]

- (a) If required by specific condition(s) in Section D of this approval, the Permittee shall prepare and maintain Preventive Maintenance Plans (PMP) within ninety (90) days after issuance of this approval, including the following information on each facility:
 - (1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;
 - (2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions;
 - (3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.

If due to circumstances beyond its control, the PMP cannot be prepared and maintained within the above time frame, the Permittee may extend the date an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Management
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

- (b) The Permittee shall implement the Preventive Maintenance Plans as necessary to ensure that lack of proper maintenance does not cause or contribute to a violation of any limitation on emissions or potential to emit.
- (c) PMP's shall be submitted to IDEM, OAM, upon request and shall be subject to review and approval by IDEM, OAM, .

C.3 Permit Amendment or Modification [326 IAC 2-7-11] [326 IAC 2-7-12]

- (a) The Permittee must comply with the requirements of 326 IAC 2-7-11 or 326 IAC 2-7-12 whenever the Permittee seeks to amend or modify this approval.

- (b) Any application requesting an amendment or modification of this approval shall be submitted to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Management
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

Any such application should be certified by the "responsible official" as defined by 326 IAC 2-7-1(34) only if a certification is required by the terms of the applicable rule

- (c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-7-11(c)(3)]

C.4 Opacity [326 IAC 5-1]

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Exemptions), opacity shall meet the following, unless otherwise stated in this approval:

- (a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings) as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

C.5 Operation of Equipment [326 IAC 2-7-6(6)]

All air pollution control equipment listed in this approval and used to comply with an applicable requirement shall be operated at all times that the emission units vented to the control equipment are in operation.

C.6 Stack Height [326 IAC 1-7]

The Permittee shall comply with the applicable provisions of 326 IAC 1-7 (Stack Height Provisions), for all exhaust stacks through which a potential (before controls) of twenty-five (25) tons per year or more of particulate matter or sulfur dioxide is emitted by using good engineering practices (GEP) pursuant to 326 IAC 1-7-3.

Testing Requirements [326 IAC 2-7-6(1)]

C.7 Performance Testing [326 IAC 3-6]

- (a) All testing shall be performed according to the provisions of 326 IAC 3-6 (Source Sampling Procedures), except as provided elsewhere in this approval, utilizing methods approved by IDEM, OAM.

A test protocol, except as provided elsewhere in this approval, shall be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Management

100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

no later than thirty-five (35) days prior to the intended test date. The Permittee shall submit a notice of the actual test date to the above address so that it is received at least two weeks prior to the test date.

- (b) All test reports must be received by IDEM, OAM within forty-five (45) days after the completion of the testing. An extension may be granted by the Commissioner, if the source submits to IDEM, OAM, a reasonable written explanation within five (5) days prior to the end of the initial forty-five (45) day period.

The documentation submitted by the Permittee does not require certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

Compliance Monitoring Requirements [326 IAC 2-7-5(1)] [326 IAC 2-7-6(1)]

C.8 Compliance Monitoring [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]

Compliance with applicable requirements shall be documented as required by this approval. The Permittee shall be responsible for installing any necessary equipment and initiating any required monitoring related to that equipment, no more than ninety (90) days after receipt of this approval. If due to circumstances beyond its control, this schedule cannot be met, the Permittee may extend the compliance schedule an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Management
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

in writing, prior to the end of the initial ninety (90) day compliance schedule, with full justification of the reasons for the inability to meet this date.

The notification which shall be submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

Corrective Actions and Response Steps [326 IAC 2-7-5] [326 IAC 2-7-6]

C.9 Compliance Monitoring Plan - Failure to Take Response Steps [326 IAC 2-7-5][326 IAC 2-7-6] [326 IAC 1-6]

- (a) The Permittee is required to implement a compliance monitoring plan to ensure that reasonable information is available to evaluate its continuous compliance with applicable requirements. This compliance monitoring plan is comprised of:
- (1) This condition;
 - (2) The Compliance Determination Requirements in Section D of this approval;
 - (3) The Compliance Monitoring Requirements in Section D of this approval;

- (4) The Record Keeping and Reporting Requirements in Section C (Monitoring Data Availability, General Record Keeping Requirements, and General Reporting Requirements) and in Section D of this approval; and
- (5) A Compliance Response Plan (CRP) for each compliance monitoring condition of this approval. CRP's shall be submitted to IDEM, OAM upon request and shall be subject to review and approval by IDEM, OAM, . The CRP shall be prepared within ninety (90) days after issuance of this approval by the Permittee and maintained on site, and is comprised of :
 - (A) Response steps that will be implemented in the event that compliance related information indicates that a response step is needed pursuant to the requirements of Section D of this approval; and
 - (B) A time schedule for taking such response steps including a schedule for devising additional response steps for situations that may not have been predicted.
- (b) For each compliance monitoring condition of this approval, appropriate response steps shall be taken when indicated by the provisions of that compliance monitoring condition. Failure to perform the actions detailed in the compliance monitoring conditions or failure to take the response steps within the time prescribed in the Compliance Response Plan, shall constitute a violation of the approval unless taking the response steps set forth in the Compliance Response Plan would be unreasonable.
- (c) After investigating the reason for the excursion, the Permittee is excused from taking further response steps for any of the following reasons:
 - (1) The monitoring equipment malfunctioned, giving a false reading. This shall be an excuse from taking further response steps providing that prompt action was taken to correct the monitoring equipment.
 - (2) The Permittee has determined that the compliance monitoring parameters established in the approval conditions are technically inappropriate, has previously submitted a request for an administrative amendment to the approval, and such request has not been denied or;
 - (3) An automatic measurement was taken when the process was not operating; or
 - (4) The process has already returned to operating within "normal" parameters and no response steps are required.
- (d) Records shall be kept of all instances in which the compliance related information was not met and of all response steps taken. In the event of an emergency, the provisions of 326 IAC 2-7-16 (Emergency Provisions) requiring prompt corrective action to mitigate emissions shall prevail.

-
- (a) When the results of a stack test performed in conformance with Section C - Performance Testing, of this approval exceed the level specified in any condition of this approval, the Permittee shall take appropriate corrective actions. The Permittee shall submit a description of these corrective actions to IDEM, OAM, within thirty (30) days of receipt of the test results. The Permittee shall take appropriate action to minimize emissions from the affected facility while the corrective actions are being implemented. IDEM, OAM shall notify the Permittee within thirty (30) days, if the corrective actions taken are deficient. The Permittee shall submit a description of additional corrective actions taken to IDEM, OAM within thirty (30) days of receipt of the notice of deficiency. IDEM, OAM reserves the authority to use enforcement activities to resolve noncompliant stack tests.
- (b) A retest to demonstrate compliance shall be performed within one hundred twenty (120) days of receipt of the original test results. Should the Permittee demonstrate to IDEM, OAM that retesting in one-hundred and twenty (120) days is not practicable, IDEM, OAM may extend the retesting deadline. Failure of the second test to demonstrate compliance with the appropriate approval conditions may be grounds for immediate revocation of the approval to operate the affected facility.

The documents submitted pursuant to this condition do not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

C.11 Monitoring Data Availability [326 IAC 2-7-6(1)] [326 IAC 2-7-5(3)]

- (a) With the exception of performance tests conducted in accordance with Section C- Performance Testing, all observations, sampling, maintenance procedures, and record keeping, required as a condition of this approval shall be performed at all times the equipment is operating at normal representative conditions.
- (b) As an alternative to the observations, sampling, maintenance procedures, and record keeping of subsection (a) above, when the equipment listed in Section D of this approval is not operating, the Permittee shall either record the fact that the equipment is shut down or perform the observations, sampling, maintenance procedures, and record keeping that would otherwise be required by this approval.
- (c) If the equipment is operating but abnormal conditions prevail, additional observations and sampling should be taken with a record made of the nature of the abnormality.
- (d) If for reasons beyond its control, the operator fails to make required observations, sampling, maintenance procedures, or record keeping, reasons for this must be recorded.
- (e) At its discretion, IDEM may excuse such failure providing adequate justification is documented and such failures do not exceed five percent (5%) of the operating time in any quarter.
- (f) Temporary, unscheduled unavailability of staff qualified to perform the required observations, sampling, maintenance procedures, or record keeping shall be considered a valid reason for failure to perform the requirements stated in (a) above.

C.12 General Record Keeping Requirements [326 IAC 2-7-5(3)][326 IAC 2-7-6]

-
- (a) Records of all required monitoring data and support information shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be kept at the source location for a minimum of three (3) years and available upon the request of an IDEM, OAM, representative.

The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a written request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.

- (b) Records of required monitoring information shall include, where applicable:
- (1) The date, place, and time of sampling or measurements;
 - (2) The dates analyses were performed;
 - (3) The company or entity performing the analyses;
 - (4) The analytic techniques or methods used;
 - (5) The results of such analyses; and
 - (6) The operating conditions existing at the time of sampling or measurement.
- (c) Support information shall include, where applicable:
- (1) Copies of all reports required by this approval;
 - (2) All original strip chart recordings for continuous monitoring instrumentation;
 - (3) All calibration and maintenance records;
 - (4) Records of preventive maintenance shall be sufficient to demonstrate that improper maintenance did not cause or contribute to a violation of any limitation on emissions or potential to emit. To be relied upon subsequent to any such violation, these records may include, but are not limited to: work orders, parts inventories, and operator's standard operating procedures. Records of response steps taken shall indicate whether the response steps were performed in accordance with the Compliance Response Plan required by Section C - Compliance Monitoring Plan - Failure to take Response Steps, of this approval, and whether a deviation from a approval condition was reported. All records shall briefly describe what maintenance and response steps were taken and indicate who performed the tasks.
- (d) All record keeping requirements not already legally required shall be implemented within ninety (90) days of approval issuance.

C.13 General Reporting Requirements [326 IAC 2-7-5(3)(C)]

- (a) The reports required by conditions in Section D of this approval shall be submitted to:

Indiana Department of Environmental Management

Compliance Data Section, Office of Air Management
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

- (b) Unless otherwise specified in this approval, any notice, report, or other submission required by this approval shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAM, on or before the date it is due.
- (c) Unless otherwise specified in this approval, any quarterly report shall be submitted within thirty (30) days of the end of the reporting period. The report do not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (d) The first report shall cover the period commencing on the date of issuance of this approval and ending on the last day of the reporting period.

SECTION D.1 FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]

- (a) one (1) shotblast machine, identified as #7, with a maximum capacity of 4.0 tons of metal castings per hour, with emissions controlled by a new baghouse, identified as baghouse I, and exhausting to stack I; and
- (b) six (6) grinders, identified as #25-30, each with a maximum capacity of 4.0 tons of metal castings per hour, with emissions controlled by a new baghouse, identified as baghouse I, and exhausting to stack I.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.1.1 Particulate Matter (PM) [326 IAC 6-3]

Pursuant to 326 IAC 6-3-2 (Process Operations), the particulate matter (PM) from the shotblaster and each of the grinders shall not exceed 10.4 pounds per hour when operating at a process weight rate of 4.0 tons of metal castings per hour each. The pounds per hour limitation was calculated with the following equation:

Interpolation and extrapolation of the data for the process weight rate up to 60,000 pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67} \quad \text{where } E = \text{rate of emission in pounds per hour; and} \\ P = \text{process weight rate in tons per hour}$$

D.1.2 Prevention of Significant Deterioration (PSD) [326 IAC 2-2]

In order to render the requirements of 326 IAC 2-2 (PSD) and 40 CFR 52.21 not applicable, the following conditions shall apply:

- (a) The PM emissions from the baghouse I controlling the shot blast machine #7 and grinders #25 - 30 shall not exceed 5.48 pounds per hour.
- (b) The PM10 emissions from the baghouse I controlling the shot blast machine #7 and grinders #25 - 30 shall not exceed 3.20 pounds per hour.

Therefore, the requirements of 326 IAC 2-2 (PSD) and 40 CFR 52.21 shall not apply.

D.1.3 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for these facilities.

Compliance Determination Requirements

D.1.4 Testing Requirements [326 IAC 2-7-6(1),(6)]

The Permittee is not required to test these facilities by this permit. However IDEM may require compliance testing when necessary to determine if the facilities are in compliance. If testing is required by IDEM, compliance with the PM and PM10 limits specified in Conditions D.1.1 and D.1.2 shall be determined by a performance test conducted in accordance with Section C - Performance Testing.

D.1.5 Particulate Matter (PM)

The baghouse identified as I for PM and PM10 control shall be in operation and control emissions from the shotblast machine #7 and grinders #25 - 30 at all times when these processes are in operation.

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

D.1.6 Visible Emissions Notations

- (a) Visible emission notations of each of the baghouse I stack exhaust shall be performed once per shift during normal daylight operations when exhausting to the atmosphere. A trained employee shall record whether emissions are normal or abnormal.
- (b) For processes operated continuously, "normal" means those conditions prevailing, or expected to prevail, eighty percent (80%) of the time the process is in operation, not counting startup or shut down time.
- (c) In the case of batch or discontinuous operations, readings shall be taken during that part of the operation that would normally be expected to cause the greatest emissions.
- (d) A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the appearance and characteristics of normal visible emissions for that specific process.
- (e) The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when an abnormal emission is observed.

D.1.7 Parametric Monitoring

The Permittee shall record the total static pressure drop across the baghouse I used in conjunction with the shotblast machine #7 and grinders #25 - 30, at least once daily when the shotblaster and the grinders are in operation when venting to the atmosphere. Unless operated under conditions for which the Compliance Response Plan specifies otherwise, the pressure drop across each of the baghouses shall be maintained within the range of 3.0 and 8.0 inches of water or a range established during the latest stack test. The Compliance Response Plan for these units shall contain troubleshooting contingency and response steps for when the pressure reading is outside of the above mentioned range for any one reading.

The instrument used for determining the pressure shall comply with Section C - Pressure Gauge Specifications, of this permit, shall be subject to approval by IDEM, OAM, and shall be calibrated at least once every six (6) months.

D.1.8 Baghouse Inspections

An inspection shall be performed each calendar quarter of all bags controlling the shotblast machine #7 and grinders #25 - 30 when venting to the atmosphere. A baghouse inspection shall be performed within three months of redirecting vents to the atmosphere and every three months thereafter. Inspections are optional when venting indoors. All defective bags shall be replaced.

D.1.9 Broken or Failed Bag Detection

In the event that bag failure has been observed.

- (a) The affected compartments will be shut down immediately until the failed units have been repaired or replaced. Within eight (8) hours of the determination of failure, response steps according to the timetable described in the Compliance Response Plan shall be initiated. For any failure with corresponding response steps and timetable not described in the Compliance Response Plan, response steps shall be devised within eight (8) hours of discovery of the failure and shall include a timetable for completion. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions).
- (b) For single compartment baghouses, failed units and the associated process will be shut down immediately until the failed units have been repaired or replaced. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions).

Record Keeping and Reporting Requirement [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.1.10 Record Keeping Requirements

- (a) To document compliance with Condition D.1.6, the Permittee shall maintain records of visible emission notations of the baghouse stack exhaust once per shift.
- (b) To document compliance with Condition D.1.7, the Permittee shall maintain the following:
 - (1) Daily records of the following operational parameters during normal operation when venting to the atmosphere:
 - (A) Inlet and outlet differential static pressure; and
 - (B) Cleaning cycle: frequency and differential pressure.
 - (2) Documentation of all response steps implemented, per event .
 - (3) Operation and Compliance Response logs, including work purchases orders, shall be maintained.
 - (4) Quality Assurance/Quality Control (QA/QC) procedures.
 - (5) Operator standard operating procedures (SOP).
 - (6) Manufacturer's specifications or its equivalent.

- (7) Equipment "troubleshooting" contingency plan.
- (8) Documentation of the dates vents are redirected.
- (c) To document compliance with Condition D.1.8, the Permittee shall maintain records of the results of the inspections required under Condition D.1.8 and the dates the vents are redirected.
- (d) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR MANAGEMENT
COMPLIANCE DATA SECTION**

**PART 70 SOURCE MODIFICATION
CERTIFICATION**

Source Name: Dalton Corporation, Kendallville Manufacturing Facility
Source Address: 200 West Ohio Street, Kendallville, Indiana 46755
Mailing Address: P.O. Box 271, Kendallville, Indiana 46755
Source Modification No.: 113-11287-00004

This certification shall be included when submitting monitoring, testing reports/results or other documents as required by this approval.

Please check what document is being certified:

- 9 Test Result (specify) _____
- 9 Report (specify) _____
- 9 Notification (specify) _____
- 9 Other (specify) _____

I certify that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

Signature:

Printed Name:

Title/Position:

Date:

Indiana Department of Environmental Management Office of Air Management

Addendum to the Technical Support Document for a Significant Source Modification to a Part 70 Operating Permit

Source Name:	Dalton Corporation, Kendallville Manufacturing Facility
Source Location:	200 West Ohio Street, Kendallville, Indiana 46755
County:	Noble
SIC Code:	3321
Operation Permit No.:	T 113-6491-00004
Operation Permit Issuance Date:	not yet issued
Significant Source Modification No.:	113-11287-00004
Permit Reviewer:	Nisha Sizemore

On September 26, 1999, the Office of Air Management (OAM) had a notice published in the New Sun, Kendallville, Indiana, stating that Dalton Corporation, Kendallville Manufacturing Facility had applied for a significant source modification to a Part 70 Operating Permit to operate a new shotblast machine and six grinders. The notice also stated that OAM proposed to issue a permit for this operation and provided information on how the public could review the proposed permit and other documentation. Finally, the notice informed interested parties that there was a period of thirty (30) days to provide comments on whether or not this permit should be issued as proposed.

On October 25, 1999, Dalton Corporation, Kendallville Manufacturing Facility submitted comments on the proposed significant source modification to the Part 70 permit. The summary of the comments is as follows:

Comment #1

The responsible official should be Daniel E. Hirsch, Plant Manager.

Response #1

The OAM has made this change in the permit.

Comment #2

Dalton has not yet been issued its title V permit. Are Conditions C.2, C.9, C.12, C.13D, D.1.6, D.1.7, and D.1.10 to be initiated ninety (90) days following approval of the modification or ninety (90) days following issuance of the Title V permit?

Response #2

These requirements are to be initiated within 90 days following the approval of the modification.

Comment #3

Section B of the permit does not contain an Emergency Provisions listing referred to in Section D.1.9.

Response #3

An emergency provision condition has been added to Section B as condition B.6

Comment #4

Regarding the History section of the technical support document, Dalton has not requested additional surface coating lines to its existing plant.

Response #4

The OAM agrees. This part of the TSD was incorrect. This does not affect the permit.

Comment #5

Regarding the enforcement issue section of the TSD, Dalton has requested an alternative emission factor be applied for its process operations limit for pouring. It is currently in compliance with the miscellaneous metal coating operations limitations. Dalton has requested limited liability for the failure to permit.

Response #5

The OAM agrees. None of these facts change any part of the permit.

Comment #6

In the TSD section titled Compliance Requirements, part 1c should read "An inspection shall be performed each calendar quarter of all bags controlling the shotblast machine #7 and grinders #25-30 when venting to the atmosphere."

Response #6

The OAM agrees. There are no changes to the permit as a result of this comment.

Indiana Department of Environmental Management Office of Air Management

Addendum to the Technical Support Document for a Significant Source Modification to a Part 70 Operating Permit

Source Name:	Dalton Corporation, Kendallville Manufacturing Facility
Source Location:	200 West Ohio Street, Kendallville, Indiana 46755
County:	Noble
SIC Code:	3321
Operation Permit No.:	T 113-6491-00004
Operation Permit Issuance Date:	not yet issued
Significant Source Modification No.:	113-11287-00004
Permit Reviewer:	Nisha Sizemore

On September 26, 1999, the Office of Air Management (OAM) had a notice published in the New Sun, Kendallville, Indiana, stating that Dalton Corporation, Kendallville Manufacturing Facility had applied for a significant source modification to a Part 70 Operating Permit to operate a new shotblast machine and six grinders. The notice also stated that OAM proposed to issue a permit for this operation and provided information on how the public could review the proposed permit and other documentation. Finally, the notice informed interested parties that there was a period of thirty (30) days to provide comments on whether or not this permit should be issued as proposed.

On October 25, 1999, Dalton Corporation, Kendallville Manufacturing Facility submitted comments on the proposed significant source modification to the Part 70 permit. The summary of the comments is as follows:

Comment #1

The responsible official should be Daniel E. Hirsch, Plant Manager.

Response #1

The OAM has made this change in the permit.

Comment #2

Dalton has not yet been issued its title V permit. Are Conditions C.2, C.9, C.12, C.13D, D.1.6, D.1.7, and D.1.10 to be initiated ninety (90) days following approval of the modification or ninety (90) days following issuance of the Title V permit?

Response #2

These requirements are to be initiated within 90 days following the approval of the modification.

Comment #3

Section B of the permit does not contain an Emergency Provisions listing referred to in Section D.1.9.

Response #3

An emergency provision condition has been added to Section B as condition B.6

Comment #4

Regarding the History section of the technical support document, Dalton has not requested additional surface coating lines to its existing plant.

Response #4

The OAM agrees. This part of the TSD was incorrect. This does not affect the permit.

Comment #5

Regarding the enforcement issue section of the TSD, Dalton has requested an alternative emission factor be applied for its process operations limit for pouring. It is currently in compliance with the miscellaneous metal coating operations limitations. Dalton has requested limited liability for the failure to permit.

Response #5

The OAM agrees. None of these facts change any part of the permit.

Comment #6

In the TSD section titled Compliance Requirements, part 1c should read "An inspection shall be performed each calendar quarter of all bags controlling the shotblast machine #7 and grinders #25-30 when venting to the atmosphere."

Response #6

The OAM agrees. There are no changes to the permit as a result of this comment.

Indiana Department of Environmental Management Office of Air Management

Technical Support Document (TSD) for a Part 70 Significant Source Modification.

Source Background and Description

Source Name:	Dalton Corporation, Kendallville Manufacturing Facility
Source Location:	200 West Ohio Street, Kendallville, Indiana 46755
County:	Noble
SIC Code:	3321
Operation Permit No.:	T 113-6491-00004
Operation Permit Issuance Date:	not yet issued
Significant Source Modification No.:	113-11287-00004
Permit Reviewer:	Nisha Sizemore

The Office of Air Management (OAM) has reviewed a modification application from Dalton Corporation, Kendallville Manufacturing Facility relating to the construction of the following emission units and pollution control devices:

- (a) one (1) shotblast machine, identified as #7, with a maximum capacity of 4.0 tons of metal castings per hour, with emissions controlled by a new baghouse, identified as baghouse I, and exhausting to stack I;
- (b) six (6) grinders, identified as #25-30, each with a maximum capacity of 4.0 tons of metal castings per hour, with emissions controlled by a new baghouse, identified as baghouse I, and exhausting to stack I.

History

On January 7, 1998, Dalton Corporation, Kendallville Manufacturing Facility submitted an application to the OAM requesting to add additional surface coating lines to their existing plant. The Part 70 permit for Dalton Corporation, Kendallville Manufacturing Facility has not yet been issued.

Enforcement Issue

The source was referred to enforcement on July 1, 1998 for alleged violations of 326 IAC 2 (Construction and Operating Permit Requirements), 326 IAC 6-3-2 (Process Operations), and 326 IAC 8-2-9 (Surface Coating Emission Limitations: Miscellaneous Metal Coating Operations). IDEM is reviewing this matter and will take appropriate action.

Stack Summary

Stack ID	Operation	Height (feet)	Diameter (feet)	Flow Rate (acfm)	Temperature (°F)
I	baghouse I controlling shotblast #7 and grinders #25-30	40	2.83	20,000	100

Recommendation

The staff recommends to the Commissioner that the Part 70 Significant Source Modification be approved. This recommendation is based on the following facts and conditions:

Unless otherwise stated, information used in this review was derived from the application and additional information submitted by the applicant.

An application for the purposes of this review was received on August 26, 1999.

Emission Calculations

The calculations submitted by the applicant have been verified and found to be accurate and correct. These calculations are provided in Appendix A of this document.

Potential To Emit of Modification

Pursuant to 326 IAC 2-1.1-1(16), Potential to Emit is defined as “the maximum capacity of a stationary source to emit any air pollutant under its physical and operational design. Any physical or operational limitation on the capacity of a source to emit an air pollutant, including air pollution control equipment and restrictions on hours of operation or type or amount of material combusted, stored, or processed shall be treated as part of its design if the limitation is enforceable by the U. S. EPA.”

This table reflects the PTE before controls. Control equipment is not considered federally enforceable until it has been required in a federally enforceable permit.

Pollutant	Potential To Emit (tons/year)
PM	298
PM-10	29.8
SO ₂	0.00
VOC	0.00
CO	0.00
NO _x	0.00

HAP's	Potential To Emit (tons/year)
chromium	less than 10
manganese	less than 10
cobalt	less than 10
nickel	less than 10
arsenic	less than 10
cadmium	less than 10
selenium	less than 10
lead	less than 10
TOTAL	less than 25

Justification for Modification

The Part 70 Operating permit is being modified through a Part 70 Significant Source Modification. This modification is being performed pursuant to 326 IAC 2-7-10.5(g).

County Attainment Status

The source is located in Noble County.

Pollutant	Status
PM-10	attainment
SO ₂	attainment
NO ₂	attainment
Ozone	attainment
CO	attainment
Lead	attainment

- (a) Volatile organic compounds (VOC) and oxides of nitrogen (NO_x) are precursors for the formation of ozone. Therefore, VOC and NO_x emissions are considered when evaluating the rule applicability relating to the ozone standards. Noble County has been designated as attainment or unclassifiable for ozone. Therefore, VOC and NO_x emissions were reviewed pursuant to the requirements for Prevention of Significant Deterioration (PSD), 326 IAC 2-2 and 40 CFR 52.21.
- (b) Noble County has been classified as attainment or unclassifiable for all criteria pollutants. Therefore, these emissions were reviewed pursuant to the requirements for Prevention of Significant Deterioration (PSD), 326 IAC 2-2 and 40 CFR 52.21.

Source Status

Existing Source PSD or Emission Offset Definition (emissions after controls, based upon 8760 hours of operation per year at rated capacity and/or as otherwise limited):

Pollutant	Emissions (tons/year)
PM	greater than 100
PM-10	greater than 100
SO ₂	less than 100
VOC	greater than 100
CO	greater than 100
NO _x	less than 100

- (a) This existing source is a major stationary source because an attainment regulated pollutant is emitted at a rate of 100 tons per year or more, and it is one of the 28 listed source categories.
- (b) These emissions are based upon airs facility quick-look data.

Potential to Emit of Modification After Issuance

The table below summarizes the potential to emit, reflecting all limits, of the significant emission units after controls. The control equipment is considered federally enforceable only after issuance of this Part 70 source modification.

	Potential to Emit (tons/year)						
Process/facility	PM	PM-10	SO ₂	VOC	CO	NO _x	HAPs
baghouse I controlling shotblast #7 and grinders #25-30	24.0	14.0	0.00	0.00	0.00	0.00	Less than 10 for single HAP and 25 for total HAPs

- (a) This modification to an existing major stationary source is not major because the emissions increase is less than the PSD significant levels. Therefore, pursuant to 326 IAC 2-2, and 40 CFR 52.21, the PSD requirements do not apply.
- (b) The PM and PM10 emissions are limited to 24 and 14 tons per year respectively, therefore, the requirements of 326 IAC 2-2 (Prevention of Significant Deterioration (PSD)) do not apply.

Federal Rule Applicability

- (a) There are no New Source Performance Standards (NSPS)(326 IAC 12 and 40 CFR Part 60) applicable to this proposed modification.
- (b) There are no National Emission Standards for Hazardous Air Pollutants (NESHAPs)(326

IAC 14 and 40 CFR Part 63) applicable to this proposed modification.

State Rule Applicability - baghouse I controlling shotblast #7 and grinders #25-30

326 IAC 6-3-2 (Process Operations)

The particulate matter (PM) from the shotblast #7 and grinders #25-30 shall be limited by the following:

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67} \quad \text{where } E = \text{rate of emission in pounds per hour and} \\ P = \text{process weight rate in tons per hour}$$

The baghouse I shall be in operation and control emissions from the shotblast #7 and grinders #25-30 at all times when any of these facilities is in operation, in order to comply with this limit.

In order to render the requirements of 326 IAC 2-2 (PSD) and 40 CFR 52.21 not applicable, the following conditions shall apply:

- (a) The PM emissions from the baghouse I controlling shotblast #7 and grinders #25-30 shall not exceed 5.48 pounds per hour.
- (b) The PM10 emissions from the baghouse I controlling shotblast #7 and grinders #25-30 shall not exceed 3.20 pounds per hour.

Therefore, the requirements of 326 IAC 2-2 and 40 CFR 52.21 shall not apply.

Compliance Requirements

Permits issued under 326 IAC 2-7 are required to ensure that sources can demonstrate compliance with applicable state and federal rules on a more or less continuous basis. All state and federal rules contain compliance provisions, however, these provisions do not always fulfill the requirement for a more or less continuous demonstration. When this occurs IDEM, OAM, in conjunction with the source, must develop specific conditions to satisfy 326 IAC 2-7-5. As a result, compliance requirements are divided into two sections: Compliance Determination Requirements and Compliance Monitoring Requirements.

Compliance Determination Requirements in Section D of the permit are those conditions that are found more or less directly within state and federal rules and the violation of which serves as grounds for enforcement action. If these conditions are not sufficient to demonstrate continuous compliance, they will be supplemented with Compliance Monitoring Requirements, also Section D of the permit. Unlike Compliance Determination Requirements, failure to meet Compliance Monitoring conditions would serve as a trigger for corrective actions and not grounds for enforcement action. However, a violation in relation to a compliance monitoring condition will arise through a source's failure to take the appropriate corrective actions within a specific time period.

The compliance monitoring requirements applicable to this modification are as follows:

1. The baghouse I controlling shotblast #7 and grinders #25-30 has applicable compliance monitoring conditions as specified below:

- (a) Visible emissions notations of the baghouse I stack exhaust shall be performed once per shift during normal daylight operations. A trained employee will record whether emissions are normal or abnormal. For processes operated continuously "normal" means those conditions prevailing, or expected to prevail, eighty percent (80%) of the time the process is in operation, not counting startup or shut down time. In the case of batch or discontinuous operations, readings shall be taken during that part of the operation that would normally be expected to cause the greatest emissions. A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the appearance and characteristics of normal visible emissions for that specific process. The Preventive Maintenance Plan for this unit shall contain troubleshooting contingency and corrective actions for when an abnormal emission is observed.
- (b) The Permittee shall record the total static pressure drop across the baghouse controlling the shotblast #7 and grinders #25-30, at least once daily when the shotblast #7 and grinders #25-30 are in operation. Unless operated under conditions for which the Preventive Maintenance Plan specifies otherwise, the pressure drop across the baghouse shall be maintained within the range of 3.0 to 8.0 inches of water or a range established during the latest stack test. The Preventive Maintenance Plan for this unit shall contain troubleshooting contingency and corrective actions for when the pressure reading is outside of the above mentioned range for any one reading.
- (c) An inspection shall be performed each calendar quarter of all bags controlling the Inclined shakeout process when venting to the atmosphere. A baghouse inspection shall be performed within three months of redirecting vents to the atmosphere and every three months thereafter. Inspections are optional when venting to the indoors. All defective bags shall be replaced.
- (d) In the event that bag failure has been observed:
 - (1) The affected compartments will be shut down immediately until the failed units have been repaired or replaced. Within eight (8) hours of the determination of failure, response steps according to the timetable described in the Compliance Response Plan shall be initiated. For any failure with corresponding response steps and timetable not described in the Compliance Response Plan, response steps shall be devised within eight (8) hours of discovery of the failure and shall include a timetable for completion. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions).
 - (2) For single compartment baghouses, failed units and the associated process will be shut down immediately until the failed units have been repaired or replaced. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions).

These monitoring conditions are necessary because the baghouse must operate properly to ensure compliance with 326 IAC 6-3 (Process Operations) and 326 IAC 2-2 (PSD).

Conclusion

The construction of this proposed modification shall be subject to the conditions of the attached proposed Part 70 Significant Source Modification No. 113-11287-00004.

Indiana Department of Environmental Management Office of Air Management

Technical Support Document (TSD) for a Part 70 Significant Source Modification.

Source Background and Description

Source Name:	Dalton Corporation, Kendallville Manufacturing Facility
Source Location:	200 West Ohio Street, Kendallville, Indiana 46755
County:	Noble
SIC Code:	3321
Operation Permit No.:	T 113-6491-00004
Operation Permit Issuance Date:	not yet issued
Significant Source Modification No.:	113-11287-00004
Permit Reviewer:	Nisha Sizemore

The Office of Air Management (OAM) has reviewed a modification application from Dalton Corporation, Kendallville Manufacturing Facility relating to the construction of the following emission units and pollution control devices:

- (a) one (1) shotblast machine, identified as #7, with a maximum capacity of 4.0 tons of metal castings per hour, with emissions controlled by a new baghouse, identified as baghouse I, and exhausting to stack I;
- (b) six (6) grinders, identified as #25-30, each with a maximum capacity of 4.0 tons of metal castings per hour, with emissions controlled by a new baghouse, identified as baghouse I, and exhausting to stack I.

History

On January 7, 1998, Dalton Corporation, Kendallville Manufacturing Facility submitted an application to the OAM requesting to add additional surface coating lines to their existing plant. The Part 70 permit for Dalton Corporation, Kendallville Manufacturing Facility has not yet been issued.

Enforcement Issue

The source was referred to enforcement on July 1, 1998 for alleged violations of 326 IAC 2 (Construction and Operating Permit Requirements), 326 IAC 6-3-2 (Process Operations), and 326 IAC 8-2-9 (Surface Coating Emission Limitations: Miscellaneous Metal Coating Operations). IDEM is reviewing this matter and will take appropriate action.

Stack Summary

Stack ID	Operation	Height (feet)	Diameter (feet)	Flow Rate (acfm)	Temperature (°F)
I	baghouse I controlling shotblast #7 and grinders #25-30	40	2.83	20,000	100

Recommendation

The staff recommends to the Commissioner that the Part 70 Significant Source Modification be approved. This recommendation is based on the following facts and conditions:

Unless otherwise stated, information used in this review was derived from the application and additional information submitted by the applicant.

An application for the purposes of this review was received on August 26, 1999.

Emission Calculations

The calculations submitted by the applicant have been verified and found to be accurate and correct. These calculations are provided in Appendix A of this document.

Potential To Emit of Modification

Pursuant to 326 IAC 2-1.1-1(16), Potential to Emit is defined as “the maximum capacity of a stationary source to emit any air pollutant under its physical and operational design. Any physical or operational limitation on the capacity of a source to emit an air pollutant, including air pollution control equipment and restrictions on hours of operation or type or amount of material combusted, stored, or processed shall be treated as part of its design if the limitation is enforceable by the U. S. EPA.”

This table reflects the PTE before controls. Control equipment is not considered federally enforceable until it has been required in a federally enforceable permit.

Pollutant	Potential To Emit (tons/year)
PM	298
PM-10	29.8
SO ₂	0.00
VOC	0.00
CO	0.00
NO _x	0.00

HAP's	Potential To Emit (tons/year)
chromium	less than 10
manganese	less than 10
cobalt	less than 10
nickel	less than 10
arsenic	less than 10
cadmium	less than 10
selenium	less than 10
lead	less than 10
TOTAL	less than 25

Justification for Modification

The Part 70 Operating permit is being modified through a Part 70 Significant Source Modification. This modification is being performed pursuant to 326 IAC 2-7-10.5(g).

County Attainment Status

The source is located in Noble County.

Pollutant	Status
PM-10	attainment
SO ₂	attainment
NO ₂	attainment
Ozone	attainment
CO	attainment
Lead	attainment

- (a) Volatile organic compounds (VOC) and oxides of nitrogen (NO_x) are precursors for the formation of ozone. Therefore, VOC and NO_x emissions are considered when evaluating the rule applicability relating to the ozone standards. Noble County has been designated as attainment or unclassifiable for ozone. Therefore, VOC and NO_x emissions were reviewed pursuant to the requirements for Prevention of Significant Deterioration (PSD), 326 IAC 2-2 and 40 CFR 52.21.
- (b) Noble County has been classified as attainment or unclassifiable for all criteria pollutants. Therefore, these emissions were reviewed pursuant to the requirements for Prevention of Significant Deterioration (PSD), 326 IAC 2-2 and 40 CFR 52.21.

Source Status

Existing Source PSD or Emission Offset Definition (emissions after controls, based upon 8760 hours of operation per year at rated capacity and/or as otherwise limited):

Pollutant	Emissions (tons/year)
PM	greater than 100
PM-10	greater than 100
SO ₂	less than 100
VOC	greater than 100
CO	greater than 100
NO _x	less than 100

- (a) This existing source is a major stationary source because an attainment regulated pollutant is emitted at a rate of 100 tons per year or more, and it is one of the 28 listed source categories.
- (b) These emissions are based upon airs facility quick-look data.

Potential to Emit of Modification After Issuance

The table below summarizes the potential to emit, reflecting all limits, of the significant emission units after controls. The control equipment is considered federally enforceable only after issuance of this Part 70 source modification.

Process/facility	Potential to Emit (tons/year)						HAPs
	PM	PM-10	SO ₂	VOC	CO	NO _x	
baghouse I controlling shotblast #7 and grinders #25-30	24.0	14.0	0.00	0.00	0.00	0.00	Less than 10 for single HAP and 25 for total HAPs

- (a) This modification to an existing major stationary source is not major because the emissions increase is less than the PSD significant levels. Therefore, pursuant to 326 IAC 2-2, and 40 CFR 52.21, the PSD requirements do not apply.
- (b) The PM and PM10 emissions are limited to 24 and 14 tons per year respectively, therefore, the requirements of 326 IAC 2-2 (Prevention of Significant Deterioration (PSD)) do not apply.

Federal Rule Applicability

- (a) There are no New Source Performance Standards (NSPS)(326 IAC 12 and 40 CFR Part 60) applicable to this proposed modification.
- (b) There are no National Emission Standards for Hazardous Air Pollutants (NESHAPs)(326

IAC 14 and 40 CFR Part 63) applicable to this proposed modification.

State Rule Applicability - baghouse I controlling shotblast #7 and grinders #25-30

326 IAC 6-3-2 (Process Operations)

The particulate matter (PM) from the shotblast #7 and grinders #25-30 shall be limited by the following:

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67} \quad \text{where } E = \text{rate of emission in pounds per hour and} \\ P = \text{process weight rate in tons per hour}$$

The baghouse I shall be in operation and control emissions from the shotblast #7 and grinders #25-30 at all times when any of these facilities is in operation, in order to comply with this limit.

In order to render the requirements of 326 IAC 2-2 (PSD) and 40 CFR 52.21 not applicable, the following conditions shall apply:

- (a) The PM emissions from the baghouse I controlling shotblast #7 and grinders #25-30 shall not exceed 5.48 pounds per hour.
- (b) The PM10 emissions from the baghouse I controlling shotblast #7 and grinders #25-30 shall not exceed 3.20 pounds per hour.

Therefore, the requirements of 326 IAC 2-2 and 40 CFR 52.21 shall not apply.

Compliance Requirements

Permits issued under 326 IAC 2-7 are required to ensure that sources can demonstrate compliance with applicable state and federal rules on a more or less continuous basis. All state and federal rules contain compliance provisions, however, these provisions do not always fulfill the requirement for a more or less continuous demonstration. When this occurs IDEM, OAM, in conjunction with the source, must develop specific conditions to satisfy 326 IAC 2-7-5. As a result, compliance requirements are divided into two sections: Compliance Determination Requirements and Compliance Monitoring Requirements.

Compliance Determination Requirements in Section D of the permit are those conditions that are found more or less directly within state and federal rules and the violation of which serves as grounds for enforcement action. If these conditions are not sufficient to demonstrate continuous compliance, they will be supplemented with Compliance Monitoring Requirements, also Section D of the permit. Unlike Compliance Determination Requirements, failure to meet Compliance Monitoring conditions would serve as a trigger for corrective actions and not grounds for enforcement action. However, a violation in relation to a compliance monitoring condition will arise through a source's failure to take the appropriate corrective actions within a specific time period.

The compliance monitoring requirements applicable to this modification are as follows:

1. The baghouse I controlling shotblast #7 and grinders #25-30 has applicable compliance monitoring conditions as specified below:

- (a) Visible emissions notations of the baghouse I stack exhaust shall be performed once per shift during normal daylight operations. A trained employee will record whether emissions are normal or abnormal. For processes operated continuously "normal" means those conditions prevailing, or expected to prevail, eighty percent (80%) of the time the process is in operation, not counting startup or shut down time. In the case of batch or discontinuous operations, readings shall be taken during that part of the operation that would normally be expected to cause the greatest emissions. A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the appearance and characteristics of normal visible emissions for that specific process. The Preventive Maintenance Plan for this unit shall contain troubleshooting contingency and corrective actions for when an abnormal emission is observed.
- (b) The Permittee shall record the total static pressure drop across the baghouse controlling the shotblast #7 and grinders #25-30, at least once daily when the shotblast #7 and grinders #25-30 are in operation. Unless operated under conditions for which the Preventive Maintenance Plan specifies otherwise, the pressure drop across the baghouse shall be maintained within the range of 3.0 to 8.0 inches of water or a range established during the latest stack test. The Preventive Maintenance Plan for this unit shall contain troubleshooting contingency and corrective actions for when the pressure reading is outside of the above mentioned range for any one reading.
- (c) An inspection shall be performed each calendar quarter of all bags controlling the Inclined shakeout process when venting to the atmosphere. A baghouse inspection shall be performed within three months of redirecting vents to the atmosphere and every three months thereafter. Inspections are optional when venting to the indoors. All defective bags shall be replaced.
- (d) In the event that bag failure has been observed:
 - (1) The affected compartments will be shut down immediately until the failed units have been repaired or replaced. Within eight (8) hours of the determination of failure, response steps according to the timetable described in the Compliance Response Plan shall be initiated. For any failure with corresponding response steps and timetable not described in the Compliance Response Plan, response steps shall be devised within eight (8) hours of discovery of the failure and shall include a timetable for completion. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions).
 - (2) For single compartment baghouses, failed units and the associated process will be shut down immediately until the failed units have been repaired or replaced. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions).

These monitoring conditions are necessary because the baghouse must operate properly to ensure compliance with 326 IAC 6-3 (Process Operations) and 326 IAC 2-2 (PSD).

Conclusion

The construction of this proposed modification shall be subject to the conditions of the attached proposed Part 70 Significant Source Modification No. 113-11287-00004.